



PE-304 Series Pendant Speaker

Feature

ดอกลำโพงขนาด 5 นิ้ว
ลำโพงแบบ 2 way

รองรับกำลังขับ 30 วัตต์
ตอบสนองความถี่ 70Hz - 20kHz

Specifications

| Model | PE-304 | Q-PE-304BK |
|------------------------|---|---|
| Enclosure | Bass-Reflex Type | |
| Rated Input | 30 W | |
| Rated Impedance | 100 V Line: 30 W, 20 W, 15 W, 10 W, 5 W 70 V Line: 30 W, 20 W, 15 W, 10 W, 5 W 8Ω | |
| Sensitivity (1 W, 1 m) | 91 dB | |
| Frequency Response | 70 Hz - 20 kHz (Peak -20dB) | |
| Speaker Component | 12 cm (5") Cone-Type + Balanced Dome-Tweeter | |
| Speaker Cord | 2-Core cabtyre cord 5 m | |
| Applicable Cable | 600 V Vinyl-insulated Cable (IV wire or HIV wire) Solid Copper Wire: $\phi 0.8$ - $\phi 1.6$ mm (Equivalent to AWG 20 - 14) 7-core twisted copper wire: 0.75 - 1.25 mm ² (Equivalent to AWG 18 - 16) | |
| Finish | Enclosure: HIPS Resin, Off-White (RAL 9010 or Equivalent Color) / Grille: Surface-Treated Steel Plate Net, Off-White (RAL 9010 or Equivalent Color), Paint | Enclosure: HIPS Resin, Black Grille: Surface-Treated Steel Plate Net, Black, Paint |
| Dimensions | $\phi 186$ x 251 mm | |
| Weight | 2.1 kg | |
| Accessory | Ceiling Bracket---1, Mounting Hanger---1, Ceiling Cover---1, Speaker Mounting Screw (4 x 16)---4 | |



PE-304



Q-PE-304BK

We supply sound, not equipment.

www.toathailand.com

f TOATHailand



Smiles for the Public