



PE-304 Series Pendant Speaker

Feature

ดอกลำโพงขนาด 5 นิ้ว
ลำโพงแบบ 2 way

รองรับกำลังขับ 30 วัตต์
ตอบสนองความถี่ 70Hz - 20kHz

Specifications

Model	PE-304	Q-PE-304BK
Enclosure	Bass-Reflex Type	
Rated Input	30 W	
Rated Impedance	100 V Line: 30 W, 20 W, 15 W, 10 W, 5 W 70 V Line: 30 W, 20 W, 15 W, 10 W, 5 W 8Ω	
Sensitivity (1 W, 1 m)	91 dB	
Frequency Response	70 Hz - 20 kHz (Peak -20dB)	
Speaker Component	12 cm (5") Cone-Type + Balanced Dome-Tweeter	
Speaker Cord	2-Core cabtyre cord 5 m	
Applicable Cable	600 V Vinyl-insulated Cable (IV wire or HIV wire) Solid Copper Wire: $\phi 0.8$ - $\phi 1.6$ mm (Equivalent to AWG 20 - 14) 7-core twisted copper wire: 0.75 - 1.25 mm ² (Equivalent to AWG 18 - 16)	
Finish	Enclosure: HIPS Resin, Off-White (RAL 9010 or Equivalent Color) / Grille: Surface-Treated Steel Plate Net, Off-White (RAL 9010 or Equivalent Color), Paint	Enclosure: HIPS Resin, Black Grille: Surface-Treated Steel Plate Net, Black, Paint
Dimensions	$\phi 186 \times 251$ mm	
Weight	2.1 kg	
Accessory	Ceiling Bracket---1, Mounting Hanger---1, Ceiling Cover---1, Speaker Mounting Screw (4 x 16)---4	



PE-304



Q-PE-304BK

We supply sound, not equipment.

www.toathailand.com

f TOAThailand



Smiles for the Public