

DESCRIPTION

The D-2012C is a 6U rack mountable Remote Console Unit designed for exclusive use with the D-2008SP Digital Mixing Processor Unit. Assigned to any desired channels inside the D-2008SP by the dedicated software, the D-2012C's 12 motorized faders and 8 rotary encoders can remotely adjust their volumes. Desired preset memories can be recalled using 8 function keys. It is equipped with 1 channel line input (stereo), which allows the audio signal to be transmitted to the D-2008SP via monitor bus. Audio signals inside the D-2008SP can be monitored via monitor bus through headphones connected to a stereo headphone output. The D-2012C can be installed on a desk with the additional use of an optional D-2012AS Console Case.

SPECIFICATIONS

* 0 dB = 0.775 V

Power Source	220 - 240 V AC, 50/60 Hz
Power Consumption	18 W
Volume Adjustment	100 mm motorized fader x 12 Rotary encoder x 8
Line Input	1 channel (stereo), +10 to -20 dB*, 10 kΩ, unbalanced, RCA Pin-jack
Headphone Output	Stereo 100 mW + 100 mW (32 Ω load), standard stereo phone-jack
Monitor Bus	1 stereo input, 1 stereo output Connector: RJ45 connector Connection cable: Shielded twisted pair (STP) Cat 5 or higher LAN cable (2 pairs of data lines) Maximum cable distance: 100 m (109.36 yd) (between D-2012C and D-2008SP)
LAN	Network I/F: 10BASE-T/100BASE-TX (Automatic-Negotiation) RJ45 connector, Connected via a switching hub Network protocol: TCP/IP Connection cable: Shielded twisted pair (STP) Cat 5 or higher LAN cable Maximum cable distance: 100 m (109.36 yd) (between D-2008SP and switching hub)
Control	RS-232C: D-sub connector (9 pins) for maintenance use
Finish	Panel: Surface-treated steel plate, Laminated with polycarbonate sheet, gray, mat Rack mounting bracket: Surface-treated steel plate, gray, mat
Dimensions	482 (W) × 266 (H) × 138 (D) mm (18.98" × 10.47" × 5.43")
Weight	6.6 kg (14.55 lb)
Accessory	Power cord (2 m (6.5 ft))1, Rack mounting screw4, Fader knob (yellow)3, Fader knob (red)3, Cord clamp (fitting screw)1
Option	Console case: D-2012AS

APPEARANCE

