

DESCRIPTION

The BS-1030W is a small, 2-way bass-reflex type speaker featuring a wide frequency range suitable for use for announcements and music playback. The BS-1030W can be used for both high-impedance and low-impedance applications. The speaker's splash-proof construction permits it to be installed under the eaves where the speaker is not directly exposed to rain.

SPECIFICATIONS

| | |
|-----------------------|---|
| Enclosure | 2-way bass-reflex type |
| Rated Input | 30 W |
| Rated Impedance | 8 Ω 100 V line: 330 Ω (30 W), 500 Ω (20 W), 670 Ω (15 W), 1 kΩ (10 W), 2 kΩ (5 W) 70 V line: 170 Ω (30 W), 250 Ω (20 W), 330 Ω (15 W), 500 Ω (10 W), 1 kΩ (5 W) |
| Sound Pressure Level | 90 dB (1 W, 1 m) |
| Frequency Response | 80 Hz - 20 kHz |
| Speaker Component | 12 cm cone-type + dome-type |
| Speaker Cord | 2-core cabtyre cord with diameter of 6 mm |
| Operating Temperature | -10 °C to +50 °C |
| Water Protection | IPX4 (can be installed vertically or horizontally.*) |
| Finish | Enclosure: ABS resin, white (RAL9010 PURE WHITE), paint Net: Surface treated steel plate, white (RAL9010 PURE WHITE), powder coating Bracket: Surface treated steel plate, white equivalent to RAL9010 PURE WHITE, powder coating |
| Dimension | 196 (W) × 290 (H) × 150 (D) mm (unit only) |
| Weight | 2.5 kg (unit only) |
| Accessory | Bracket×1, Bracket mounting screw×2, Bracket mounting washer×2 |
| Option | Mounting bracket: SP-420 Applicable bracket: WCB-13W, SP-410 Applicable stand: ST-16A |

* Install with the front facing downward. Note that the splash-proof capability will be lost if installed face-up. The logo mark needs to be located in the lower section when the speaker is installed vertically, and on the right side of the speaker (as viewed from the front) when installed horizontally.

APPEARANCE

