

DESCRIPTION

The H-2 is a dome-shaped, small surface-mount 2-way speaker that ensures quality sound reproduction. The angle of speaker can be adjusted for 360 degrees parallel to the mounting surface.

SPECIFICATIONS

| | |
|-----------------------|---|
| Enclosure Type | Sealed type |
| Power Handling | 120 W (continuous program/4 Ω), 40 W (continuous pink noise/4 Ω) |
| Rated Input | 12 W (16 Ω, high impedance) |
| Rated Impedance | 4 Ω, 16 Ω 100 V line: 830 Ω (12 W), 1.7 kΩ (6 W), 3.3 kΩ (3 W) 70 V line: 420 Ω (12 W), 830 Ω (6 W), 1.7 kΩ (3 W), 3.3 kΩ (1.5 W) |
| Sensitivity | 88 dB (1 W, 1 m) at installation in 1/2 free sound field (Measured by installing the unit in the center of a wall.) |
| Frequency Response | 100 Hz - 20 kHz |
| Speaker Component | Low frequency: 10 cm cone-type, High frequency: Balanced dome-type |
| Input Terminal | Detachable screw terminal, (+)/(-) 2 each (for bridging connection) |
| Usable Cable | Solid cable, stranded cable: 0.2 - 2.5 mm ² (AWG No. 24 - 14 equivalent) |
| Finish | Punched net: Steel plate, white, paint Frame: Fire-resistant ABS resin, white, paint Base frame: Steel plate |
| Dimensions | ∅268 × 111 mm |
| Weight | 2.1 kg (including base frame) |
| Accessory | Base frame1, Electrical box mounting screw1 set |
| Usable Electrical Box | 1-gang type (with cover)(*1) |
| Other Feature | Angle of speaker: 360 degrees adjustable in parallel to the mounting surface |

(*1) Without using an electrical box, mounting the supplied base frame directly to a wall or ceiling allows the speaker installation.

APPEARANCE

