

## DESCRIPTION

The H-3 is a wall-mountable 2-way speaker that provides horizontally-wide dispersion.

## SPECIFICATIONS

|                         |   |
|-------------------------|---|
| Enclosure               | Sealed type   |
| Power Handling Capacity | 150 W (Continuous program/8 Ω)<br>50 W (Continuous pink noise/8 Ω)  |
| Rated Input             | 30 W (16 Ω, high impedance)   |
| Rated Impedance         | 8 Ω, 16 Ω<br>100 V line: 330 Ω (30 W), 670 Ω (15 W), 1.3 kΩ (7.5 W)<br>70 V line: 170 Ω (30 W), 330 Ω (15 W), 670 Ω (7.5 W), 1.3 kΩ (3.75 W)  |
| Sensitivity             | 89 dB (1 W, 1 m) at installation in 1/2 free sound field<br>(Measured by installing the unit in the center of a wall.)  |
| Frequency Response      | 100 Hz – 20 kHz (–10 dB) at installation in 1/2 free sound field<br>(Measured by installing the unit in the center of a wall.)  |
| Crossover Frequency     | 4 kHz   |
| Speaker Component       | Low frequency: 10 cm cone-type × 2<br>High frequency: 2.5 cm dome-type (neodymium magnet)   |
| Input Terminal          | Detachable screw terminal, (+)/(-) 2 each (for bridging connection)   |
| Usable Cable            | Solid cable, stranded cable: 0.2 – 2.5 mm <sup>2</sup> (AWG No.24 – 14)   |
| Finish                  | Enclosure: Fire-resistant ABS resin, black<br>Front frame: Fire-resistant ABS resin, off-white, paint<br>Punched net: Steel plate, off-white, paint<br>Base frame: Steel plate, plating |
| Dimensions              | 295 (W) × 318 (H) × 129 (D) mm  |
| Weight                  | 3.3 kg  |
| Accessory               | Front grille .....1, Base frame .....1, Electrical box mounting screw .....1 set  |
| Usable Electrical Box   | 2-gang type   |

## APPEARANCE

